## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **LISTING OF CLAIMS:**

1. (Currently Amended) A mirror structure comprising:

a self-deforming mirror mounted on a passive flexible support structure said mirror having a piezo electric actuator that is bonded to a mirror substrate, and including electrodes for applying electric fields to selected regions of the actuator layer to thereby deform the mirror substrate without applying forces to the support structure.

the support structure comprising, one or more passive flexible support elements attached to the piezo electric actuator of arranged to provide a supporting surface on which the self-deforming mirror is mounted, wherein the support structure is arranged to enable a deformation response in the self-deforming mirror mounted thereon such that the self deforming mirror is operable to adopt a predetermined deformation profile by the application of electrical fields across regions of the piezo-electric actuator.

2. (Previously Presented) The mirror structure as claimed in claim 1, wherein a plurality of said passive flexible support elements are spatially arranged to support the self-deforming mirror from below, with each of the support elements having an end shaped for providing support to the self-deforming mirror and a

Page 4

flexible portion that connects the supporting end of the support element to a body

portion of the support structure.

3. (Previously Presented) The mirror structure as claimed in claim 2,

wherein at least one of the support elements is generally L-shaped such that one leg

of the L-shape provides the flexible portion and the other leg of the L-shape provides

the supporting end of the support element.

4. (Cancelled)

5. (Previously Presented) The mirror structure as claimed in claim 25,

wherein each of the support elements is comprising:

a plurality of spatially-distributed support elements positioned so as to be in

supportive contact with a different electrode of the self-deforming mirror mounted

thereon actuator.

6. (Previously Presented) The mirror structure as claimed in claim 2,

wherein the support elements are formed of compliant epoxy/rubber material.

7. (Previously Presented) The mirror structure as claimed in claim 2,

wherein the supporting end of each support element is formed of compliant

epoxy/rubber material and the remainder portion of each support element is formed

of metal material.

8. (Previously Presented) A deformable mirror holder comprising a body with a receiving portion for receiving a deformable mirror wherein the receiving portion is defined by a passive flexible support structure such that, in use, the support structure provides a supporting surface to the mirror,

wherein the support structure comprises a plurality of discrete flexible support elements spatially arranged to support the mirror substrate from below, with each of the support elements having an end shaped to provide support to the mirror substrate and a flexible portion that connects the element's end to the holder's body, and

wherein the support elements are formed of a conducting compliant foam such that they permit electrical connection to a number of mirror electrodes.

- 9. (Previously Presented) The mirror structure as claimed in claim 2, wherein the support elements are formed as integral parts of the body portion of the support structure.
- 10. (Previously Presented) The mirror structure as claimed in claim 6, wherein the compliance of compliant material selected to form at least a portion of each of the support elements varies according to an established position of the support element in the support structure.
- 11. (Previously Presented) The mirror structure as claimed in claim 10, wherein the compliance of the selected compliant material varies according to the

Page 6

distance of the respective support element from the edge of a supported mirror

substrate.

12. (Previously Presented) The mirror structure as claimed in claim 6,

wherein the compliance of each of the support elements varies according to the

position of the support element in the support structure.

13. (Previously Presented) The mirror structure as claimed in claim 12.

wherein the compliance of each of the support elements varies according to the

length of the support element.

14. (Previously Presented) The mirror structure as claimed in claim 12,

wherein the compliance of each of the support elements varies according to the

cross-sectional area of the support element.

15. (Previously Presented) The mirror structure as claimed in claim 12,

wherein the compliance of each of the support elements varies according to the

compliance of the compliant material used to form the support element.

16. (Previously Presented) The mirror structure as claimed in claim 1,

wherein the support structure comprises a generally solid unitary structure with

compliant characteristics, which unitary structure is arranged to extend across the

entire width of the self-deforming mirror surface for support thereof from below.

Page 7

17. (Previously Presented) The mirror structure as claimed in claim 16,

wherein the unitary structure is formed of epoxy/rubber material.

18. (Previously Presented) The mirror structure as claimed in claim 16,

wherein the unitary structure includes a number of hole sections for permitting

access to a number of electrodes of the self-deforming mirror when mounted

thereon.

19. (Previously Presented) The mirror structure as claimed in claim 16,

wherein the unitary structure includes a number of metallic interconnections

permitting connection to a number of electrodes of the self-deforming mirror when

mounted thereon, which metallic interconnections are arranged to respond to the

deformation of the unitary structure in use.

20. (Previously Presented) The mirror structure as claimed in claim 16,

wherein the compliance of the unitary structure varies according to the distance from

the edge of the unitary structure.

21. (Previously Presented) The mirror structure as claimed in claim 20.

wherein the unitary structure comprises a plurality of discrete annuli each composed

of a compliant material having a different compliance.

Page 8

22. (Previously Presented) The mirror structure as claimed in claim 20,

wherein the thickness of the unitary structure varies according to distance from the

edge of the unitary structure.

23. (Previously Presented) The mirror structure as claimed in claim 16,

wherein the unitary structure is composed of a compliant material having

substantially uniform compliance and a thickness of the unitary structure varies

according to distance from the edge of the unitary structure.

24. (Canceled)

25. (Currently Amended) The [[mirror]] structure as claimed in claim 38

[[1]], wherein the self deforming mirror comprises a reflective surface provided on

the substrate, the morphing [[and a]] layer of deformable material attached to the

substrate that is operable to deform the mirror the piezo electric actuator comprising

a piezoelectric element and electrodes for applying operating potentials thereto.

26. (Previously Presented) The mirror structure as claimed in claim 25,

comprising a cooling system.

27. (Previously Presented) The mirror structure as claimed in claim 26,

wherein said cooling system comprises a number of interconnecting conduits which

are joined to form a continuous through-passage, enabling coolant to be admitted

and circulated therethrough.

- 28. (Previously Presented) The mirror structure as claimed in claim 24, further comprising a tip-tilt stage.
  - 29. (Canceled)
  - 30. (Canceled)
- 31. (Previously Presented) The mirror structure as claimed in claim 1, wherein the required deformation response for the self-deforming mirror includes a resonant frequency for the self-deforming mirror mounted on the support structure.
- 32. (Previously Presented) The mirror structure as in claim 1, wherein the deformation response for the self-deforming mirror includes a required stroke characteristics for the self-deforming mirror mounted on the support structure.
- 33. (Previously Presented) The mirror structure as claimed in claim 25, wherein the self-deforming mirror is a bimorph self-deforming mirror, the piezoelectric actuator comprising having at least one layer of deformable material piezoelectric material as said piezoelectric element.
- 34. (Previously Presented) The mirror structure as claimed in claim 25, wherein at least some of the support elements are disposed in equi-spaced

Attorney Docket No. 1033963-000014

Application No. 10/520,425

Page 10

relationships in a circular arrangement, each positioned so as to be in contact with

one or more mirror of the electrodes when in use.

35. (Previously Presented) The mirror structure of claim 25, wherein the

electrode includes a common electrode disposed between the mirror substrate and

the piezoelectric element.

36. (Previously Presented) The mirror structure of claim 35, wherein the

common electrode step is disposed on an upper surface of the piezoelectric element

and an array of electrodes are disposed on a lower surface of the piezoelectric

element.

37. (Previously Presented) The mirror structure of claim 36, wherein the

array of electrodes is disposed between the piezoelectric element and the one or

more passive flexible support elements.

38. (Currently Amended) A mirror structure comprising:

a self-deforming mirror; and

a passive flexible support structure comprising one or more passive flexible

support elements on which the self-deforming mirror is supported,

wherein the support structure is arranged to enable a deformation response in

the self-deforming mirror thereon, and

wherein the self-deforming mirror comprises a mirror substrate that defines a

reflective mirror surface, and at least one morphing layer bonded to the substrate

and actuable to deform the mirror substrate by applying loads thereto other than through without applying loads to the flexible support elements.